

**PENTAX**

## R-200 Series

EFFICIENT ACCURACY AT YOUR FINGERS!

- 350m reflectorless EDM range
- 2" and 5" models
- Adjustable laser plummet



**INCREASED  
PRODUCTIVITY  
FASTER  
TURNAROUND**



Model	R-202NE	R-205NE
<b>Telescope</b>	Magnification	30 x
	Effective aperture	45mm (EDM45mm)
	Resolving power	3.0"
	Field of view	2.6 % (1° 30')
	Minimum focus	1.0 m
	Focus	Manual
<b>Distance measurement</b>	Visible laser: Class III a (3R) (Reflectorless) / Class II (2) (Prism, sheet)	
<b>Measurement range</b> (Good conditions) (*3)	Reflectorless (*1)	1.5 ~ 350 m
	Reflector sheet (*2)	1.5 ~ 600 m (800 m)
	Mini Prism	1.5 ~ 1,100 m (2,000 m)
	1 P	1.5 ~ 3,000 m
	3 P	1.5 ~ 4,500 m
<b>Accuracy</b>	Prism / Reflector sheet	1.5 ~ 10 m: $\pm (3 + 2 \text{ ppm} \times D) \text{ mm} / 10 \text{ m} \sim \pm (2 + 2 \text{ ppm} \times D) \text{ mm}$ , Quick: $\pm (3 + 2 \text{ ppm} \times D) \text{ mm}$ (*5)
	Reflectorless	1.5 ~ 300 m: $\pm (5 + 2 \text{ ppm} \times D) \text{ mm} / 300 \text{ m} \sim \pm (7 + 10 \text{ ppm} \times D) \text{ mm}$
	Minimum count	0.1 mm (Fine mode) / 1 mm (Normal mode) / 10mm (Track mode)
<b>Measuring time</b> (*4)	Repeat meas. Normal (1 mm)	Prism / Reflector sheet 2.0 sec - Reflectorless 2.0 sec
	Quick (1 mm)	Prism / Reflector sheet 1.2 sec (*5)
	Track (10 mm)	Prism / Reflector sheet 0.4 sec - Reflectorless 0.4 sec
	Initial meas. Normal (1 mm)	Prism / Reflector sheet 2.5 sec - Reflectorless 2.4 sec
	Quick (1 mm)	Prism / Reflector sheet 1.7 sec (*5)
	Track (10 mm)	Prism / Reflector sheet 2.5 sec - Reflectorless 2.5 sec
<b>Angle measurement</b>	Measurement method	Absolute rotary encoder
	Direction method	Vertical / Horizontal angle: 2 sides
	Minimum count	1" / 5" selectable
	Accuracy (ISO 17123-3)	2" / 5"
<b>Compensator</b>	Axis	Single
	Range	$\pm 3'$
<b>Target screw</b>	1 speed	
<b>Sensitivity of vials</b>	Plate level	30" / 1 mm
	Circular level	8' / 2 mm
<b>Plummet</b>	Laser Plummet	
<b>Base</b>	Detachable	
<b>Dust &amp; water resistance</b>	IP56 (instrument only)	
<b>Ambient temperature</b>	-20°C ~ +50°C / -4°F ~ 122°F (working range)	
<b>Tripod thread</b>	5/8" x 11	
<b>Dimensions / Weight</b>	Dimensions	180 (W) x 342 (H) x 177 (L) mm
	Weight (incl. battery)	5.7 kg
	Carrying case	250 (W) x 365 (H) x 425 (L) mm
<b>Battery pack</b>	Power source	Ni-MH 4300 mAh (rechargeable) DC 6.0 V
	Operation time	Approx. 7.0 hrs (ETH + EDM) / 15hrs (ETH) with approx. 2.2 hrs of charging time
	Weight	380 g
<b>Battery charger and AC adapter</b>	Input Voltage	AC 100 ~ 240 V
	Output Voltage	DC 7.5 V
	Weight	280 g
<b>Data Process</b>	Data recording method	Internal Memory
	Coordinates data (*6)	20,000
	Special function	PowerTopoLite
	I / F	RS-232C
<b>Display / keyboard</b>	Display type	Graphic LCD / 20 characters x 8 lines / 240 x 96 pixels
	Quantity	double
	Keys	22 each (12 numeric / 5 function / 5 special)
	Display back light	Intensity settings: 10 steps
<b>Laser Pointer</b>	Yes	
<b>Date clock</b>	Yes	

\*1 The measurement range and accuracy of reflectorless, and time required to measure may vary by the shape, size of surface area and reflection rate of the target and its environment. The measurement range of reflectorless is determined by the white side of the Kodak Gray Card. (KODAK is a trademark of Eastman Kodak Company)

\*2 Reflector sheet: PENTAX genuine Reflector sheet

\*3 The measurement range may vary by conditions of the environment.

Normal conditions: 20km visibility with slight shimmer

Good conditions: 40km visibility, overcast, no heat, no shimmer and moderate wind.

\*4 EDM measuring time is determined in good conditions. It may take longer than usual to measure the distance exceeding 4000m in prism mode and 300m in reflectorless mode. Also the measurement time in reflectorless mode is influenced by the shape, size and surface area and reflection rate of the target and its environment.

\*5 Quick mode, which functions with prism and reflector sheet, is effective only under normal mode (1mm) and up to 500m.

\*6 Number of points to be recorded may vary by usage.

Maximum number of point to be recorded per job site: 3000 points

Maximum number of job file to be recorded: 50 job files

Maximum data points to be sent from PC to the instrument: 3000 points

### TI Asahi Co., Ltd.

#### International Sales Department

4-3-4 Ueno Iwatsuki-Ku, Saitama-Shi

Saitama-Ken, 339-0073 Japan

Tel.: +81-48-793-0118

Fax: +81-48-793-0128

E-mail: International@tiasahi.com

[www.pentaxsurveying.com/en/](http://www.pentaxsurveying.com/en/)

Your Official Pentax Dealer

### DANGER

LASER RADIATION - DO NOT STARE INTO BEAM OR VIEW DIRECTLY WITH OPTICAL INSTRUMENT INTO SUNLIGHT.  
620-690 nm/4.75mW max.  
CLASS IIIa LASER PRODUCT  
Laserclass IIIa, conform FDA 21 CFR Ch. 1 § 1040

### CAUTION

LASER RADIATION - DO NOT STARE INTO BEAM  
620-690 nm/0.95mW max.  
CLASS II LASER PRODUCT  
Laserclass II, conform FDA 21 CFR Ch. 1 § 1040



The CE marking assures that this product complies with the requirements of the EC directive for safety.



### JSIMA

Japan Surveying Instruments Manufacturers' Association  
Member symbol of the Japan Surveying Instruments Manufacturers' Association representing the high quality surveying products.